

Technical Information

www.addivant.com

Effective: April 2013

WESTON® 399 phosphite

Phosphite Antioxidant

Description

WESTON® 399 phosphite is a versatile phosphite stabilizer which is useful in a large number of polymers such as HDPE, LLDPE, SBR, ABS, PVC and others.

Chemical Structure

Trisnonylphenyl Phosphite⁽¹⁾ C₄₅H₆₉O₃P Chemical Abstract Number: 26523-78-4

Typical physical properties of WESTON® 399 phosphite

- Jerom Jeroyanam Jeropanina ar million	· · ·
Appearance	Clear liquid
Specific Gravity @ 25°C - 15.5°C	0.980-0.992
Color (Pt - Co)	75 max.
Flash Point (Pensky - Martens Closed Cup)	196°C (385°F)
Density (lb/gal @ 25°C) (g/ml @ 25°C)	8.2 0.98
Vapor Pressure @ 6 mm/Hg	245°C (472°F)
Formula Weight (g/mol)	688
Viscosity, cps @ 60°C (140°F)	250
Acid No. (mg KOH/g)	0.25 max
Refractive Index @ 25°C (77°F)	1.5250 - 1.5280
Free Nonylphenol (%)	4.0 max
Phosphorus Content (%)	4.1-4.5
Chlorine Content	<25 ppm
Free Phenol	<50 ppm
Specific Heat mcal/mg°C	0.4
Thermal Conductivity gcal/(sec)(cm ²)(°C/cm)	0.0003
Auto-ignition Temperature	439°C (822°F)

WESTON® 399 phosphite contains approximately 0.75% by weight of Triisopropanolamine, (CAS # 122-20-3).

The information contained herein relates to a specific AddivantTM product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of AddivantTM standard terms and conditions of sale under which the product is sold by AddivantTM. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ANY AND ALL SUCH REPRESENTATIONS AND WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.



Technical Information

www.addivant.com

Effective: April 2013

Solubility

Soluble in most common aprotic organic solvents

Water: <0.1

Applications

WESTON® 399 phosphite is a versatile liquid phosphite stabilizer which improves color and processing stability as well as end use of a variety of polymers such as HDPE, LLDPE, SBR, ABS, PVC and others.

Product Features

- Low color and low nonylphenol content
- Improves color and processing stability during recovery, drying, compounding, processing and end use.
- Synergism is realized when this product is combined with other stabilizers such as hindered phenols.
- May be added alone or in combination with the monomers and/or in antioxidant emulsions during recovery and/or during compounding

Food Contact Regulatory Status

WESTON® 399 phosphite complies with 21 CFR 178.2010 and with EU Directive 2002/72/EC for use in all polymers. Consult the regulations for limitations/restrictions before use. For details please contact Addivant™ Regulatory Affairs Polymer Additives.

Viscosity versus Temperature

WESTON® 399 phosphite can be heated to facilitate transfer in-plant. The following viscosity versus temperature table can be used for proper selection of metering and pumping equipment. The following data shows a wide range of temperatures, however, the maximum recommended storage temperature is 80°C.

Viscosity, cps	Temperature / °C
15,000	15
6,000	25
1,300	40
525	50
395	55
250	60
115	70
80	80
50	90
32	100
21	110
18	120

The information contained herein relates to a specific AddivantTM product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of AddivantTM standard terms and conditions of sale under which the product is sold by AddivantTM. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ANY AND ALL SUCH REPRESENTATIONS AND WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.



Technical Information

www.addivant.com

Effective: April 2013

Storage and Handling

The product may be stored at least one (1) year in sealed containers. Containers should be stored in a cool, dry area. Extended storage at elevated temperatures or exposure to direct heat could decrease product shelf life. Containers should be kept sealed when not in use. If stored outside in cold weather, the drums should be warmed to facilitate pouring. Open drums should be used as soon as possible (within a maximum of 4 months) to avoid hydrolysis, especially during humid weather.

For additional handling and toxicological information consult the Addivant[™] Material Safety Data Sheet.