CYASORB® UV-2908 LIGHT STABILIZER

TYPICAL PROPERTIES

Appearance White to off white powder

Melting point 60°C

PERFORMANCE BENEFITS

- · Excellent solubility in polyolefins
- Superior Long Term Heat Ageing (LTHA)
- Minimal color contribution
- Low volatility
- Good solubility/migration balace
- Excellent compatibility with UV absorbers, HALS and thioesters
- FDA sanctioned up to 0.5% in polyolefins

APPLICATIONS

- Flame Retardant Polyolefins
- Polypropylene
- TPO
- Polyesters
- PVC

SAFETY AND HANDLING

Before handling this material, refer to the Safety Data Sheet for important safety, health and environmental information.

SHIPPING CLASSIFICATION

Please refer to the Transport Information section on the Safety Data Sheet




Figure 1. LTHA Performance of CYASORB® UV-2908 Profax 6401 Polypropylene Resin, 125 micron film, 0.10% 2,4,6-tri-t-butylphenol





Figure 2. UV stabilization performance of CYASORB® UV-2908 Polypropylene Tape (2 x 100 micron) UV Exposure Study



All trademarks are the property of their respective owners. © 2016 Cytec Industries Inc. The ® indicates a Registered Trademark in the United States and the ™ indicates a trademark in the United States. The mark may also be registered, subject of an application for registration, or a trademark in other countries.

Disclaimer: Solvay SA in its own name and on behalf of its affiliated companies (collectively, "Solvay") decline any liability with respect to the use made by anyone of the information contained herein. The information contained herein represents Solvay's best knowledge thereon without constituting any express or implied guarantee or warranty of any kind (including, but not limited to, regarding the accuracy, the completeness or relevance of the data set out herein). Nothing contained herein shall be construed as conferring any license or right under any patent or other intellectual property rights of Solvay or of any third party. The information relating to the products is given for information purposes only. No guarantee or warranty is provided that the product and/or information is adapted for any specific use, performance or result and that product and/or information do not infringe any Solvay and/or third party intellectual property rights. The user should perform its own tests to determine the suitability for a particular purpose. The final choice of use of a product and/or information as well as the investigation of any possible violation of intellectual property rights of Solvay and/or third parties remains the sole responsibility of the user.

Solvay

custinfo@solvay.com Tel: +1.973.357.3100 Fax: +1.973.357.3100

